

## Rodamiento de agujas 15BTM2116-JTEKT - 15BTM2116-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/15btm2116-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type		
							With open ends	With closed end	
15	21	16	13.3	9.80	13.6	23 000	<b>15BTM2116</b>		

  

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (F6)		Housing bore dia. (N7)		With open ends	With closed end
		min.	max.	min.	max.		
—	—	14.989	15.000	20.972	20.993	14	16

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	4549250088650
Diámetro interior	15 mm
Diámetro exterior	21 mm
Espesor	16 mm
Peso	14 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE