

Rodamiento de agujas BHTM1512A-JTEKT - BHTM1512A-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bhtm1512a-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.		Caged type With open ends	With closed end
15	22	12	9.3	6.90	7.95	23 000		BHTM1512A	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	14.989	15.000	21.991 ⁽⁴⁾	22.012 ⁽⁴⁾	12	14

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952470207
Diámetro interior	15 mm
Diámetro exterior	22 mm
Espesor	12 mm
Peso	12 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE