

Rodamiento de agujas MHKM1520-JTEKT - MHKM1520-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/mhkm1520-jtekt>

Drawn cup needle roller bearings



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|----------------|---------------------------|-----------------|
| F_w | D | C | b min. | C_r | C_{0r} | Oil lub. | Caged type | |
| | | | With open ends | | | With open ends | | With closed end |
| 15 | 22 | 20 | 17.3 | 14.2 | 18.8 | 23 000 | MHKM1520 | |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 14.989 | 15.000 | 21.972 | 21.993 | 20 | 23 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 3663952470245 |
| Diámetro interior | 15 mm |
| Diámetro exterior | 22 mm |
| Espesor | 20 mm |
| Peso | 23 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE