

## Rodamiento de agujas 16MKM2212-JTEKT - 16MKM2212-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/16mkm2212-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{10}$	Oil lub.	Caged type	
			With open ends	With closed end			With open ends	With closed end
16	22	12	9.3	7.80	9.80	22 000	16MKM2212	

  

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	21.991 <sup>4)</sup>	22.012 <sup>4)</sup>	11	12

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952470290
Diámetro interior	16 mm
Diámetro exterior	22 mm
Espesor	12 mm
Peso	12 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE