


Rodamiento de agujas 16MKM2216-JTEKT - 16MKM2216-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/16mkm2216-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾	
F _w	D	C	b min.	C ₀	Oil lub.	Caged type With open ends With closed end	
16	22	16	13.3	10.7	15.1	22 000	16MKM2216

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)		
With open ends	With closed end	Shaft dia. (d6) min.	Housing bore dia. (N7) min.	max.	min.	max.	With open ends	With closed end
—	—	15.989	16.000	21.972	21.993		15	17

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952470337
Diámetro interior	16 mm
Diámetro exterior	22 mm
Espesor	16 mm
Peso	17 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE