

## Rodamiento de agujas BHTM1612-JTEKT - BHTM1612-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bhtm1612-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
F <sub>w</sub>	D	C	b min.	C <sub>0</sub>	C <sub>0r</sub>	Oil lub.	Caged type	
							With open ends	With closed end
16	24	12	—	8.00	8.45	21 000	<b>BHTM1612</b>	

  

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6)		Housing bore dia. (N7)		With open ends	With closed end
		min.	max.	min.	max.		
—	—	15.989	16.000	23.972	23.993	15	—

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952470351
Diámetro interior	16 mm
Diámetro exterior	24 mm
Espesor	12 mm
Peso	15 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE