


Rodamiento de agujas MHKM1616-JTEKT - MHKM1616-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/mhkm1616-jtekt>

Drawn cup needle roller bearings 

Caged type
With closed end



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.		Caged type	
16	24	16	13.3	12.2	14.9	21 000		With open ends	With closed end
									MHKM1616

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	23.991 ⁽⁴⁾	24.012 ⁽⁴⁾	20	23

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952470375
Diámetro interior	16 mm
Diámetro interior	0.63" inch
Diámetro exterior	24 mm
Diámetro exterior	0.945" inch
Espesor	16 mm
Espesor	0.63" inch
Peso	23 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE