


Rodamiento de agujas BHM1720A-JTEKT - BHM1720A-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bhm1720a-jtekt>

Drawn cup needle roller bearings 

Full complement type
With open ends



BH, BHM

Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F _w	D	C	b min.	C ₁₀	C ₉₀	Oil lub.	Caged type	
							With open ends	With closed end
17	24	20	—	19.0	21.9	7 200		

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6)		Housing bore dia. (H7)		With open ends	With closed end
		min.	max.	min.	max.		
BHM1720A		16.983 ³⁾	16.994 ³⁾	23.985 ⁴⁾	24.006 ⁴⁾	27	—

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	4549250294792
Diámetro interior	17 mm
Diámetro exterior	24 mm
Espesor	20 mm
Peso	27 g
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE