

Rodamiento de agujas 18BM2412-JTEKT - 18BM2412-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/18bm2412-jtekt>

Drawn cup needle roller bearings Koyo

Full complement type
With open ends

BM, BHM

| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|----------|---------------------------|-----------------|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type | |
| | | | | | | | With open ends | With closed end |
| 18 | 24 | 12 | 9.6 | 10.8 | 19.2 | 6 900 | | |

| | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | | | |
|-----------------|-----------------------------|-----------------|-------------------------|--------|-------------------|-----------------|----|----|
| | Full complement type | | Housing bore dia. (N7) | | With open ends | With closed end | | |
| | With open ends | With closed end | Shaft dia. (H6) min. | max. | min. | max. | | |
| 18BM2412 | | | 17.989 | 18.000 | 23.972 | 23.993 | 17 | 20 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 3616060465320 |
| Diámetro interior | 18 mm |
| Diámetro exterior | 24 mm |
| Espesor | 12 mm |
| Peso | 17 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE