

Rodamiento de agujas 18BTM2412-JTEKT - 18BTM2412-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/18btm2412-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾		
F _w	D	C	b min.	C ₀	C _{0r}	Oil lub.	Caged type		
								With open ends	With closed end
18	24	12	—	7.90	10.9	20 000	18BTM2412		

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	17.989	18.000	23.991 ⁽⁴⁾	24.012 ⁽⁴⁾	12	—

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952470627
Diámetro interior	18 mm
Diámetro exterior	24 mm
Espesor	12 mm
Peso	12 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE