

Rodamiento de agujas BTM1817A-JTEKT - BTM1817A-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/btm1817a-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F _w	D	C	b min.	C ₁₀	C ₉₀	Oil lub.	Caged type	
							With open ends	With closed end
18	25	17	—	12.2	17.7	19 000	BTM1817A	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	17.989	18.000	24.991 ⁽⁴⁾	25.012 ⁽⁴⁾	20	—

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952470696
Diámetro interior	18 mm
Diámetro exterior	25 mm
Espesor	17 mm
Peso	20 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE