

Rodamiento de agujas 20MKM2616-JTEKT - 20MKM2616-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/20mkm2616-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_r	C_{0r}	Oil lub.		Caged type	
20	26	16	13.3	12.4	20.3	18 000		With open ends	With closed end
									20MKM2616

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	19.987	20.000	25.972	25.993	19	21

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952470856
Diámetro interior	20 mm
Diámetro exterior	26 mm
Espesor	16 mm
Peso	21 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE