

## Rodamiento de agujas BTM202725-JTEKT - BTM202725-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/btm202725-jtekt>

### Drawn cup needle roller bearings



| Boundary dimensions (mm) |    |    |        | Basic load ratings (kN) |                 | Limiting speeds (min <sup>-1</sup> ) | Bearing No. <sup>2)</sup>                       |
|--------------------------|----|----|--------|-------------------------|-----------------|--------------------------------------|---|
| F <sub>w</sub>           | D  | C  | b min. | C <sub>r</sub>          | C <sub>0r</sub> | Oil lub.                             | Caged type<br>With open ends    With closed end |
| 20                       | 27 | 25 | —      | 22.1                    | 36.6            | 18 000                               | <b>BTM202725</b>                                |

  

| Full complement type |                 | Recommended dimensions (mm) |        |                             |        | (Refer.) Mass (g) |                 |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends       | With closed end | Shaft dia. (φ6) min.        | max.   | Housing bore dia. (N7) min. | max.   | With open ends    | With closed end |
| —                    | —               | 19.987                      | 20.000 | 26.972                      | 26.993 | 33                | —               |

## CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| N° Ean13          | 3663952470962 |
| Diámetro interior | 20 mm         |
| Diámetro exterior | 27 mm         |
| Espesor           | 25 mm         |
| Peso              | 33 g          |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE