

Rodamiento de agujas BTM2220A-JTEKT - BTM2220A-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/btm2220a-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_{10}	C_{90}	Oil lub.	Caged type With open ends With closed end
22	29	20	17.3	16.2	26.7	16 000	BTM2220A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	21.987	22.000	28.972	28.993	30	33

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	4549250004117
Diámetro interior	22 mm
Diámetro exterior	29 mm
Espesor	20 mm
Peso	30 g
Envasado	-

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE