

Rodamiento de agujas BTM2420-JTEKT - BTM2420-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/btm2420-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F _w	D	C	b min.	C ₀	C _{0r}	Oil lub.	Caged type With open ends With closed end
24	31	20	17.3	17.7	29.4	15 000	BTM2420

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	23.987	24.000	30.967	30.992	31	35

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952471266
Diámetro interior	24 mm
Diámetro exterior	31 mm
Espesor	20 mm
Peso	31 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE