


## Rodamiento de agujas MKM2512-JTEKT - MKM2512-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/mkm2512-jtekt>

### Drawn cup needle roller bearings

Caged type  
With closed end



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.		Caged type With open ends	With closed end
25	32	12	9.3	9.05	12.4	14 000			<b>MKM2512</b>

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	31.967	31.992	19	21

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952471334
Diámetro interior	25 mm
Diámetro exterior	32 mm
Espesor	12 mm
Peso	21 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE