

Rodamiento de agujas BTM2526-JTEKT - BTM2526-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/btm2526-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|--|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 25 | 32 | 26 | 23.3 | 23.7 | 43.1 | 14 000 | BTM2526 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 24.987 | 25.000 | 31.967 | 31.992 | 42 | 48 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 3663952471419 |
| Diámetro interior | 25 mm |
| Diámetro exterior | 32 mm |
| Espesor | 26 mm |
| Peso | 42 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE