

Rodamiento de agujas BHTM2510A-JTEKT - BHTM2510A-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bhtm2510a-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F _w	D	C	b min.	C _r	C _{0r}	Oil lub.	Caged type With open ends With closed end
25	33	10	—	8.90	10.3	14 000	BHTM2510A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	32.989 ⁽⁴⁾	33.014 ⁽⁴⁾	18	—

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952471433
Diámetro interior	25 mm
Diámetro exterior	33 mm
Espesor	10 mm
Peso	18 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE