

Rodamiento de agujas 28BTM3516-JTEKT - 28BTM3516-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/28btm3516-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F _w	D	C	b min.	C ₁₀	C ₉₀	Oil lub.	Caged type With open ends With closed end
28	35	16	13.3	15.9	26.2	13 000	28BTM3516

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	27.987	28.000	34.967	34.992	28	31

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	4549250107122
Diámetro interior	28 mm
Diámetro exterior	35 mm
Espesor	16 mm
Peso	28 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE