

## Rodamiento de agujas 30BTM3716BM-JTEKT - 30BTM3716BM-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/30btm3716bm-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
F <sub>w</sub>	D	C	b min.	C <sub>0</sub>	C <sub>0r</sub>	Oil lub.	Caged type With open ends With closed end
30	37	16	13.3	17.1	29.3	12 000	<b>30BTM3716BM</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	29.987	30.000	36.967	36.992	30	33

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952471815
Diámetro interior	30 mm
Diámetro exterior	37 mm
Espesor	16 mm
Peso	30 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE