

## Rodamiento de agujas BHTM3220A-JTEKT - BHTM3220A-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bhtm3220a-jtekt>

### Drawn cup needle roller bearings



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
F <sub>w</sub>	D	C	b min.	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Caged type With open ends    With closed end
32	42	20	17.3	23.4	34.8	11 000	BHTM3220A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	31.984	32.000	41.989 <sup>(4)</sup>	42.014 <sup>(4)</sup>	57	64

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	4549250003233
Diámetro interior	32 mm
Diámetro exterior	42 mm
Espesor	20 mm
Peso	57 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE