

Rodamiento de agujas BTM4025-JTEKT - BTM4025-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/btm4025-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F _w	D	C	b min.	C ₁₀	C ₉₀	Oil lub.		Caged type	
40	50	25	—	36.2	66.2	9 100		With open ends	With closed end
								BTM4025	

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	39.984	40.000	49.967	49.992	91	—

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952472621
Diámetro interior	40 mm
Diámetro interior	1.575" inch
Diámetro exterior	50 mm
Diámetro exterior	1.969" inch
Espesor	25 mm
Espesor	0.984" inch
Peso	91 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE