

Rodamiento de agujas BTM505816J-JTEKT - BTM505816J-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/btm505816j-jtekt>

Drawn cup needle roller bearings



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾	
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.	Caged type	With closed end
50	58	16	—	21.9	43.8	7 500	With open ends	BTM505816J

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	Shaft dia. (H6) max.	Housing bore dia. (H7) min.	Housing bore dia. (H7) max.	With open ends	With closed end
—	—	49.984	50.000	57.961	57.991	54	—

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952472867
Diámetro interior	50 mm
Diámetro exterior	58 mm
Espesor	16 mm
Peso	54 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE