

Rodamiento rodillos NN3038-JTEKT - NN3038-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nn3038-jtekt>

Double-row cylindrical roller bearings 



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds (min ⁻¹) | | Bearing No. | |
|--------------------------|-----|----|-----|-------------------------|-----|------------------|--------------------------------------|----------|------------------|--------------|
| d | D | B | r | F _w | C | C ₁₀₇ | Grease lub. | Oil lub. | Cylindrical bore | Tapered bore |
| 190 | 290 | 75 | 2.1 | — | 265 | 598 | 1 900 | 2 300 | NN3038 | |

| | | Mounting dimensions (mm) | | | | | | (Refer.) Mass (kg) | |
|------------------|--------------|--------------------------|------|----------------|------|----------------|------|--------------------|--------------|
| Cylindrical bore | Tapered bore | d _a | | D _s | | r _s | | Cylindrical bore | Tapered bore |
| | | min. | max. | min. | max. | min. | max. | | |
| | | 201 | — | — | 279 | 267 | 2 | 17.5 | 17.1 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952473376 |
| Diámetro interior | 190 mm |
| Diámetro exterior | 290 mm |
| Espesor | 75 mm |
| Peso | 17600 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE