

Rodamiento rodillos NNU4944K-JTEKT - NNU4944K-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nnu4944k-jtekt>

Double-row cylindrical roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.	
d	D	B	r	F _w	E _a	C	C ₁₀₇	Grease lub.	Oil lub.	NN Cylindrical bore Tapered bore
220	300	80	2.1	244	—	501	1 220	1 700	2 000	

Mounting dimensions (mm)		d _a		D _a	r _a		(Refer.) Mass (kg)		
Cylindrical bore	Tapered bore	min.	max.	min.	max.	min.	max.	Cylindrical bore	Tapered bore
	NNU4944K	231	241	248	289	—	2	16.7	16.0

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952473444
Diámetro interior	220 mm
Diámetro exterior	300 mm
Espesor	80 mm
Peso	16000 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE