


## Rodamiento rodillos NNU4948K-JTEKT - NNU4948K-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nnu4948k-jtekt>

Double-row cylindrical roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.	
d	D	B	r <sub>min</sub>	F <sub>w</sub>	E <sub>a</sub>	C	C <sub>107</sub>	Grease lub.	Oil lub.	NN Cylindrical bore Tapered bore
240	320	80	2.1	263		588	1340	1800	1900	

Mounting dimensions (mm)		d <sub>s</sub>		D <sub>s</sub>	r <sub>s</sub>		(Refer.) Mass (kg)		
min.	max.	min.	max.	min.	max.	min.	max.	Cylindrical bore	Tapered bore
		251	260	269	309	—	2	18.0	17.2

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952473482
Diámetro interior	240 mm
Diámetro exterior	320 mm
Espesor	80 mm
Peso	17200 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE