


Rodamiento rodillos NN3005K-JTEKT - NN3005K-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nn3005k-jtekt>

Double-row cylindrical roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F_w</i>	<i>E_a</i>	<i>C</i>	<i>C₀₇</i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
25	47	16	0.6	—	41.3	25.7	30.0	14 000	17 000	—	NN3005K

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d_a</i>		<i>D_a</i>		<i>r_a</i>	Cylindrical bore	Tapered bore	
		min.	max.	min.	max.				
		29	—	—	43	42	0.127	0.123	

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952473543
Diámetro interior	25 mm
Diámetro exterior	47 mm
Espesor	16 mm
Peso	123 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE