

## Rodamiento rodillos NN3006-JTEKT - NN3006-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nn3006-jtekt>

Double-row cylindrical roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.	
d	D	B	r	F <sub>w</sub>	C	C <sub>107</sub>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
30	55	19	1	—	48.5	36.8	12 000	14 000	NN	NN3006

  

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	d <sub>a</sub>		d <sub>s</sub>		D <sub>s</sub>	r <sub>s</sub>		
		min.	max.	min.	max.	min.	max.	Cylindrical bore	Tapered bore
		35	—	—	50	49	1	0.198	0.192

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	4549250031632
Diámetro interior	30 mm
Diámetro interior	1.181" inch
Diámetro exterior	55 mm
Diámetro exterior	2.165" inch
Espesor	19 mm
Espesor	0.748" inch
Peso	198 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE