


Rodamiento rodillos NN3006K-JTEKT - NN3006K-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nn3006k-jtekt>

Double-row cylindrical roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F_w</i>	<i>E_a</i>	<i>C</i>	<i>C₀₂</i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
30	55	19	1	—	48.5	36.8	44.1	12 000	14 000	—	NN3006K

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d_a</i>		<i>D_a</i>		<i>r_a</i>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		35	—	—	50	49	1	0.198	0.192

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952473567
Diámetro interior	30 mm
Diámetro exterior	55 mm
Espesor	19 mm
Peso	192 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE