

Rodamiento rodillos NN3009K-JTEKT - NN3009K-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nn3009k-jtekt>

Double-row cylindrical roller bearings ————— **Koyo**



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.	
d	D	B	r	C	C ₁₀₇	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore	
45	75	23	1	67.5	53.4	8 300	9 900		NN3009K	

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	d _a		D _a		r _a		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		50	—	—	70	69	1	0.404	0.382

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952473628
Diámetro interior	45 mm
Diámetro exterior	75 mm
Espesor	23 mm
Peso	382 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE