


## Rodamiento rodillos NN3013K-JTEKT - NN3013K-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nn3013k-jtekt>

Double-row cylindrical roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>E<sub>a</sub></i>	<i>C</i>	<i>C<sub>02</sub></i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
65	100	26	1.1	—	91	74.5	111	6 000	7 200	—	—
				Mounting dimensions (mm)				(Refer.) Mass (kg)			
Cylindrical bore		Tapered bore		<i>d<sub>a</sub></i> min.	<i>d<sub>a</sub></i> max.	<i>D<sub>a</sub></i> min.	<i>D<sub>a</sub></i> max.	<i>r<sub>a</sub></i> min.	<i>r<sub>a</sub></i> max.	Cylindrical bore	Tapered bore
				71.5	—	—	93.5	92	1	0.728	0.705

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952473703
Diámetro interior	65 mm
Diámetro exterior	100 mm
Espesor	26 mm
Peso	705 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE