


Rodamiento rodillos NN3072K-JTEKT - NN3072K-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nn3072k-jtekt>

Double-row cylindrical roller bearings ————— **Koyo**



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F_w</i>	<i>E_a</i>	<i>C</i>	<i>C₀₇</i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
360	540	134	5	—	493	1500	3090	830	990	—	—
				Mounting dimensions (mm)				(Refer.) Mass (kg)			
NNU		Tapered bore		<i>d_a</i> min.	<i>d_a</i> max.	<i>D_a</i> min.	<i>D_a</i> max.	<i>r_a</i> min.	<i>r_a</i> max.	Cylindrical bore	Tapered bore
				380	—	—	520	497	4	107	104

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952474113
Diámetro interior	360 mm
Diámetro exterior	540 mm
Espesor	134 mm
Peso	104000 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE