

Rodamiento de agujas 20NQ3315D-JTEKT - 20NQ3315D-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/20nq3315d-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
20	—	33	15	14.0	16.9	21 000	20NQ3315D	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
	d ₂	D ₂	r ₂	—	—	—		
	max.	max.	max.	—	—	—		
	—	29	0.6	0.052	—	—		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952477473
Diámetro interior	20 mm
Diámetro interior	0.787" inch
Diámetro exterior	33 mm
Diámetro exterior	1.299" inch
Espesor	15 mm
Espesor	0.591" inch
Peso	52 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE