

## Rodamiento de agujas NQ22-16-JTEKT - NQ22-16-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/nq22-16-jtekt>

Machined ring needle roller bearings  **Koyo**  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring	
22	—	30	16	—	12.7	20.2	21 000	<b>NQ22/16</b>
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
	d <sub>a</sub>	D <sub>a</sub>	r <sub>a</sub>	—	—	—		
	max.	max.	max.	—	0.032	—		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952477510
Diámetro interior	22 mm
Diámetro exterior	30 mm
Espesor	16 mm
Peso	32 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE