


Rodamiento de agujas NA4901R-JTEKT - NA4901R-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/na4901r-jtekt>

Machined ring needle roller bearings  **Koyo**
F_w 29 ~ 37 mm

With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|----|----|----|-------------------------|-----------------|------------------------------------|--|--------------------|-------------|
| F _w | d | D | B | C _r | C ₁₀ | C _{10r} | Oil lub. | Without inner ring | |
| 16 | 12 | 24 | 13 | — | 10.2 | 11.8 | 27 000 | — | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| NA4901R | | | | 14 | 22 | 0.3 | 0.018 | 0.027 | IRM121613 |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952477824 |
| Diámetro interior | 12 mm |
| Diámetro exterior | 24 mm |
| Espesor | 13 mm |
| Peso | 27 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE