

Rodamiento rodillos RNA4904ARD-1-JTEKT - RNA4904ARD-1-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/rna4904ard-1-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|---|----|----|-------------------------|-----------------|--|--------------------|--------------|
| F _w | d | D | B | C _r | C _{0r} | Oil lub. | Without inner ring | |
| 25 | — | 37 | 17 | 21.5 | 25.7 | 17 000 | Without inner ring | RNA4904ARD-1 |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | |
| With inner ring | | | | Without inner ring | With inner ring | Without inner ring | | |
| d _a | | | | 0.054 | — | — | | |
| D _o | | | | — | — | — | | |
| r _a | | | | — | — | — | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952482415 |
| Diámetro interior | 25 mm |
| Diámetro exterior | 37 mm |
| Espesor | 17 mm |
| Peso | 54 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE