

Rodamiento rodillos NQ283720D-JTEKT - NQ283720D-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nq283720d-jtekt>

Machined ring needle roller bearings 
F_W 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|----------------|----------------|----------------|-------------------------|-----------------|------------------------------------|--|--------------------|-------------|
| F _w | d | D | B | B ₁ | C _r | C _{0r} | Oil lub. | Without inner ring | |
| 28 | — | 37 | 20 | — | 20.6 | 34.7 | 16 000 | NQ283720D | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| | d _i | D _i | r _s | — | — | | | | |
| | max. | max. | max. | 35 | 0.3 | | | | |
| | | | | | 0.056 | | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952482514 |
| Diámetro interior | 28 mm |
| Diámetro exterior | 37 mm |
| Espesor | 20 mm |
| Peso | 56 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE