

## Rodamiento rodillos NQ29-20-JTEKT - NQ29-20-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nq29-20-jtekt>

Machined ring needle roller bearings  **Koyo**  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No. Without inner ring
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>10</sub>	Oil lub.			
29	—	38	20	—	20.4	34.8	16 000	NQ29/20	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d <sub>2</sub>	D <sub>2</sub>	r <sub>a</sub>	0.056	—				
	min.	max.	max.	—	—				
	—	34	0.6	—	—				

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952482613
Diámetro interior	29 mm
Diámetro exterior	38 mm
Espesor	20 mm
Peso	56 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE