


Rodamiento rodillos NQI28-30-JTEKT - NQI28-30-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nqi28-30-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring	
F _w	d	D	B	C _r	C _{10r}	Oil lub.			
32	28	42	30	34.4	61.6	14 000	—	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
NQI28/30				30	40	0.3	0.104	0.141	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952482804
Diámetro interior	28 mm
Diámetro exterior	42 mm
Espesor	30 mm
Peso	141 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE