

Rodamiento rodillos NQS32-22-JTEKT - NQS32-22-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nqs32-22-jtekt>

Machined ring needle roller bearings

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{0r}	Oil lub.		
32	25	47	22	0.3	31.2	41.4	14 000	NQS32/22

Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.
With inner ring	d_1	D_1	r_1	Without inner ring	With inner ring	
	27	45	0.3	0.123	0.167	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952482835
Diámetro interior	32 mm
Diámetro exterior	47 mm
Espesor	22 mm
Peso	123 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE