


Rodamiento de agujas NQIS25-22-JTEKT - NQIS25-22-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/nqis25-22-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
32	25	47	22	31.2	41.4	14 000	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
NQIS25/22				27	45	0.123	0.167	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952482842
Diámetro interior	25 mm
Diámetro exterior	47 mm
Espesor	22 mm
Peso	167 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE