


## Rodamiento rodillos NA4906UU-JTEKT - NA4906UU-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/na4906uu-jtekt>

Machined ring needle roller bearings   
F<sub>W</sub> 29 – 37 mm  
With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No. Without inner ring	
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring		
35	30	47	17	18	0.3	19.5	25.3	5 700	—
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				d <sub>1</sub> max.	D <sub>1</sub> max.	r <sub>a</sub> max.	Without inner ring	With inner ring	
NA4906UU				32	45	0.3	—	0.105	IRM303518

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952482873
Diámetro interior	30 mm
Diámetro exterior	47 mm
Espesor	17 mm
Peso	105 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE