

Rodamiento rodillos NQ37-20-JTEKT - NQ37-20-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nq37-20-jtekt>

Machined ring needle roller bearings  **Koyo**
F_w 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|----------------|----------------|----------------|-------------------------|-----------------|------------------------------------|--|--------------------|-------------|
| F _w | d | D | B | C _r | C _{0r} | Oil lub. | | Without inner ring | |
| 37 | 32 | 47 | 20 | 26.0 | 45.1 | | 13 000 | NQ37/20 | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| | d ₂ | D ₂ | r ₂ | 0.079 | 0.114 | | | | |
| | min. | max. | max. | | | | | | |
| | 34 | 45 | 0.3 | | | | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 3663952482965 |
| Diámetro interior | 37 mm |
| Diámetro exterior | 47 mm |
| Espesor | 20 mm |
| Peso | 79 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE