

## Rodamiento rodillos NQ40-15AD-JTEKT - NQ40-15AD-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nq40-15ad-jtekt>

Machined ring needle roller bearings  **Koyo**  
F<sub>w</sub> 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) |                |                |                | Basic load ratings (kN) |                 |                                    | Limiting speeds <sup>1)</sup> (min <sup>-1</sup> ) |           | Bearing No.<br>Without inner ring |
|--------------------------|----------------|----------------|----------------|-------------------------|-----------------|------------------------------------|--|-----------|-----------------------------------|
| F <sub>w</sub>           | d              | D              | B              | C <sub>r</sub>          | C <sub>10</sub> | Oil lub.                           |  |           |                                   |
| 40                       | —              | 50             | 15             | —                       | 21.0            | 35.1                               | 12 000   | NQ40/15AD |                                   |
| Mounting dimensions (mm) |                |                |                | (Refer.) Mass (kg)      |                 | (Refer.) Applicable inner ring No. |  |           |                                   |
| With inner ring          |                |                |                | Without inner ring      | With inner ring |                                    |  |           |                                   |
|                          | d <sub>a</sub> | D <sub>a</sub> | r <sub>a</sub> | 0.063                   | —               |                                    |  |           |                                   |
|                          | max.           | max.           | max.           | —                       | —               |                                    |  |           |                                   |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| N° Ean13          | 3663952483023 |
| Diámetro interior | 40 mm         |
| Diámetro exterior | 50 mm         |
| Espesor           | 15 mm         |
| Peso              | 63 g          |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE