


Rodamiento rodillos NQI42-30-JTEKT - NQI42-30-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nqi42-30-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F _w	d	D	B	B ₁	r	C _r	C _{10r}	Oil lub.	Without inner ring	Without inner ring
47	42	57	30	—	0.6	44.0	96.1	10 000	—	—
				Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
				With inner ring	d ₁ min.	D ₁ max.	r _a max.	Without inner ring	With inner ring	Applicable inner ring No.
				NQI42/30	46	53	0.6	—	0.219	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952483252
Diámetro interior	42 mm
Diámetro exterior	57 mm
Espesor	30 mm
Peso	219 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE