


Rodamiento rodillos NA4909UU-JTEKT - NA4909UU-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/na4909uu-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 – 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F _w	d	D	B	C _r	C ₁₀	Oil lub.	Without inner ring	Without inner ring	
52	45	68	22	37.7	56.8	3 800	—	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
NA4909UU				49	64	0.6	—	0.285	IRM455223

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3616060465689
Diámetro interior	45 mm
Diámetro exterior	68 mm
Espesor	22 mm
Peso	285 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE