


## Rodamiento rodillos NA4910R-JTEKT - NA4910R-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/na4910r-jtekt>

Machined ring needle roller bearings  **Koyo**  
F<sub>W</sub> 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.		
F <sub>w</sub>	d	D	B	B <sub>1</sub>	r	C <sub>r</sub>	C <sub>10</sub>	Oil lub.	Grease lub.	Without inner ring	With inner ring	
58	50	72	22		0.5	48.0	80.0	7 900		—	—	
					Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
					With inner ring	d <sub>i</sub>	D <sub>e</sub>	r <sub>a</sub>	Without inner ring	With inner ring		
					max.	max.	max.					
					NA4910R	54	68	0.5	0.172	0.276	IRM505822	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952483559
Diámetro interior	50 mm
Diámetro exterior	72 mm
Espesor	22 mm
Peso	276 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE