

Rodamiento rodillos RNA4913-JTEKT - RNA4913-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/rna4913-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_w 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. Without inner ring |
|--------------------------|----------------|----------------|----------------|----------------|-------------------------|-----------------|------------------------------------|--|----------------|-----------------------------------|
| F _w | d | D | B | B ₁ | C _r | C ₁₀ | Oil lub. | | | |
| 72 | 65 | 90 | 25 | 1 | 66.1 | 114.0 | 6 400 | | RNA4913 | |
| Mounting dimensions (mm) | | | | | [Refer.] Mass (kg) | | [Refer.] Applicable inner ring No. | | | |
| With inner ring | | | | | Without inner ring | With inner ring | | | | |
| | d ₁ | D ₁ | r _s | | 0.307 | 0.450 | IRM65725 | | | |
| | max. | max. | max. | | | | | | | |
| | 70 | 85 | 1 | | | | | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952483771 |
| Diámetro interior | 72 mm |
| Diámetro exterior | 90 mm |
| Espesor | 25 mm |
| Peso | 307 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE