


## Rodamiento rodillos NA5916-JTEKT - NA5916-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/na5916-jtekt>

Machined ring needle roller bearings   
F<sub>W</sub> 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>10r</sub>	Oil lub.	Without inner ring	Without inner ring	
90	80	110	40	114.0	232.0	5 100	—	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				d <sub>i</sub>	D <sub>e</sub>	r <sub>a</sub>	Without inner ring	With inner ring	
NA5916				85	105	1	0.681	1.39	IRM809040

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952483993
Diámetro interior	80 mm
Diámetro exterior	110 mm
Espesor	40 mm
Peso	1090 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE