


## Casquillos de agujas BAM1014-IKO - BAM1014-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam1014-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g																														
	Standard	Mass (Ref.) g	Closed end																																								
15.875 ( $\frac{5}{8}$ )	---	---	---	---	---	---	---	---	---	---	---	---	---																														
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="4">Standard mounting dimensions</th> <th rowspan="2">Basic dynamic load rating C</th> <th rowspan="2">Basic static load rating C<sub>0</sub></th> <th rowspan="2">Allowable rotational speed<sup>(1)</sup></th> <th rowspan="2">Assembled inner ring</th> </tr> <tr> <th>F<sub>w</sub></th> <th>D</th> <th>C</th> <th colspan="2">Shaft dia. h8</th> <th colspan="2">Housing bore dia. J7</th> </tr> </thead> <tbody> <tr> <td>15.875 <math>\frac{1}{4}</math></td> <td>20.638 <math>\frac{3}{4}</math></td> <td>22.221 <math>\frac{7}{8}</math></td> <td>1.3</td> <td>15.875</td> <td>15.864</td> <td>20.650</td> <td>20.629</td> <td>10 700</td> <td>17 500</td> <td>25 000</td> <td>IRB 714</td> </tr> </tbody> </table>														Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring	F <sub>w</sub>	D	C	Shaft dia. h8		Housing bore dia. J7		15.875 $\frac{1}{4}$	20.638 $\frac{3}{4}$	22.221 $\frac{7}{8}$	1.3	15.875	15.864	20.650	20.629	10 700	17 500	25 000	IRB 714
Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring																																	
F <sub>w</sub>	D	C	Shaft dia. h8		Housing bore dia. J7																																						
15.875 $\frac{1}{4}$	20.638 $\frac{3}{4}$	22.221 $\frac{7}{8}$	1.3	15.875	15.864	20.650	20.629	10 700	17 500	25 000	IRB 714																																

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952172910
Diámetro interior	15.88 mm
Diámetro exterior	20.64 mm
Espesor	22.22 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE